

v310a

Description	The 5 GHz Faint Radio Population at VLBI Resolutions
Antennas	At-Cd-Ho-Mp-Pa
Start	344 02:00:00
Stop	344 14:02:30
PI	S.P. Ellingsen

Setup lba6cm-2p-2IF-64MHz:

Station Modes	At Mp Pa
Channel 1	IFP#1-L0 4784 - 4848 MHz USB RCP
Channel 2	IFP#1-HI 4784 - 4848 MHz USB LCP
Channel 3	IFP#2-L0 4848 - 4912 MHz USB RCP
Channel 4	IFP#2-HI 4848 - 4912 MHz USB LCP
DAS 1 Skyfreq	4816 MHz
DAS 1 Skyfreq	4880 MHz
Bandwidth	64 MHz
DAS Mode	64MHz_[nf].pro (telescope)
Station Modes	Cd Ho
Channel 1	IFP#1 4784 - 4848 MHz USB RCP
Channel 2	IFP#2 4784 - 4848 MHz USB LCP
DAS 1 Skyfreq	4816 MHz
Bandwidth	64 MHz
DAS Mode	64MHz_[nf].pro (telescope)

Ftp: <ftp://ftp.atnf.csiro.au/pub/people/vlbi/v310/v310a>

Comments:

This project is aiming to test the feasibility of in-beam phase referencing with the LBA at 5 GHz. It involves cycling between the three strongest 5 GHz sources in the ATESP field and a nearby ICRF2 source. The ICRF2 source should (hopefully) be strong enough to be used as a real-time fringe checker if necessary.

Observing comments for each antenna:

At	Cd	Ho	Mp	Pa
----	----	----	----	----

Observing Logs

[Parkes onsource flagging](#)
[ATCA onsource flagging](#)
[Mopra onsource flagging](#)
[Mopra Tsys \(plot\)](#)
[Parkes Tsys](#)

Weather

[ATCA Weather](#)
[Mopra Weather](#)
[Parkes Weather](#)

From:

<http://www.atnf.csiro.au/vlbi/dokuwiki/> - **ATNF VLBI Wiki**

Permanent link:

<http://www.atnf.csiro.au/vlbi/dokuwiki/doku.php/lbaops/lbadec2009/v310a>

Last update: **2015/12/18 16:38**

