

## vt02f5 Setup:\

<b>Antennas</b>	At-Mp-Pa-Ho-Cd-Ti
<b>Start</b>	70 19:30:00
<b>Stop</b>	70 20:35:00
<b>PI</b>	LBA fringe-check
<b>Channel 1</b>	2252 - 2268 MHz USB RCP
<b>Channel 2</b>	2268 - 2284 MHz USB RCP
<b>Bandwidth</b>	16 MHz
<b>Recorder</b>	Disk through S2
<b>DAS Mode</b>	<a href="http://vsop.pro">vsop.pro</a>
<b>S2 Mode</b>	32x4-2
<b>Buggary Cable</b>	out

\ Ftp: <ftp://ftp.atnf.csiro.au/pub/people/vlbi/vt02/vt02f/vt02f5> \ --\ \

## Comments:\

\ Fringe check for v181e\ \ Record on /data/internal\ \ Use RecordMode "Channel 1,2" in disk0 or (-c oox in vsib\_record)\ \ On S2 type "uic feedthru on" if not already enabled \ \

- [Tid Notes](#)

From:  
<https://www.atnf.csiro.au/vlbi/dokuwiki/> - **ATNF VLBI Wiki**

Permanent link:  
<https://www.atnf.csiro.au/vlbi/dokuwiki/doku.php/lbaops/lbamar2006/vt02f5?rev=1141953313>

Last update: **2015/12/18 16:38**