

ATCA Bi-static Radar Observing Instructions

Telescope

caacor setup?

DAS

- Make sure the “8 bit” cable is connected between DAS “DigiOut” board and VSIC
- Set VSIC to mode (Huygens)
- Configure DAS using `msl_f.pro` profile. This gives a 4 MHz band, offset from central ATCA IF frequency by XX MHz.

Recording

Record the data using the command:

```
vsib_record -m 2 -bits 8 -w 4 -x -o EXPERIMENTNAME -t Xh
```

Where “X” is the recording time in hours. There is an alias to allow this to be simplified to:

```
radarrecord -o EXPERIMENTNAME -t Xh
```

Realtime spectra

Create realtime spectra to be loaded onto the interactive webpage:

```
fauto_ipp -n 80000 -sp1 45000 -sp2 55000 -t 60s -online -noplot -dump -  
command "scp %s kaputar:atca.spec"
```

Create realtime spectra in “.rdr” format and copy to the ATNF ftp area (using ``vsib_send``):

```
fauto_ipp -n 4194304 -sp1 2516582 -sp2 2621440 -t 1s -online -dump -radar -  
command "vsib_send -p 33333 -H draco %s" -noplot -lo 7159
```

This requires a `vsib_recv` process running on “draco”, on port 33333:

```
vsib_recv -p 33333
```

Last update: 2021/01/28 17:18 southernhemisphereradar:observing_instructions https://www.atnf.csiro.au/vlbi/dokuwiki/doku.php/southernhemisphereradar/observing_instructions?rev=1611814732

From:
<https://www.atnf.csiro.au/vlbi/dokuwiki/> - **ATNF VLBI Wiki**

Permanent link:
https://www.atnf.csiro.au/vlbi/dokuwiki/doku.php/southernhemisphereradar/observing_instructions?rev=1611814732

Last update: **2021/01/28 17:18**

